

### Indicator lights with reflector

rear mounting, rotation proof  
Option: waterproof IP64 / IP67 / IP68

### Signalleuchten mit Reflektor

von hinten montierbar, verdrehsicher  
Option: wasserdicht IP64 / IP67 / IP68


### Voyants lumineux avec réflecteur

montage par l'arrière, anti-rotation  
Option: étanche IP64 / IP67 / IP68

133R

134R

138R



3D Step-file available on request

Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“									
Type / Typ / Type	Body / Körper / Corps		Accessories / Zubehör / Accessoires			Light source Lichtquelle Source lum.	Resistor Widerstand Résistance		
LED inside reflector LED innerhalb Reflektor LED à l'intérieur du réflecteur	Protection Schutzart Protection	Surface Oberfläche Surface	washer	Nut Mutter Ecrou			LED 3 mm	Code	V
<b>133R</b>  LED terminals LED-Anschlüsse Fils des LED	<b>4</b> IP 64  <b>7</b> IP 67  <b>8</b> IP 68	<b>U</b> Brass, blackened Messing, geschwärzt Laiton, noircie	<b>1</b> Lock-washer 	<b>H</b> with hex nut mit 6kant Mutter avec écrou 6-pans 	<b>Y33U</b> 4200 mcd <b>Y30U</b> 1200 mcd <b>Y301</b> 30 mcd 	<b>0</b> without ohne sans	<b>A</b> 5 20  <b>B</b> 12 20  <b>D</b> 24 20  <b>DB</b> 24 15  <b>E</b> 28 20  <b>EB</b> 28 14		
		<b>9</b> Brass, olive drab * Messing, braunoliv * Laiton, olivebrun *			<b>G41N</b> 17600 mcd <b>G51N</b> 10320 mcd <b>G301</b> 40 mcd 				
						<b>R33U</b> 4000 mcd <b>R30U</b> 1500 mcd <b>R301</b> 8 mcd 	<b>W37N</b> 13350 mcd <b>W36N</b> 6900 mcd <b>W32N</b> 3745 mcd 		
<b>134R</b>  Solder lugs Lötösen Contact à souder	<b>4</b> IP 64  <b>7</b> IP 67  <b>8</b> IP 68	<b>1</b> Brass, blackened Messing, geschwärzt Laiton, noircie	<b>1</b> Lock-washer 	<b>H</b> with hex nut mit 6kant Mutter avec écrou 6-pans 	<b>R33U</b> 4000 mcd <b>R30U</b> 1500 mcd <b>R301</b> 8 mcd 			<b>W37N</b> 13350 mcd <b>W36N</b> 6900 mcd <b>W32N</b> 3745 mcd 	<b>RG36</b> common cathode only series 133R 138R for 24V only 15mA for 28V only 14mA 
						<b>2</b> Brass, nickel plated Messing, vernickelt Laiton, nickelée	<b>2</b> decorative washer 		
<b>9</b> Brass, olive drab * Messing, braunoliv * Laiton, olivebrun *									
			<b>138R</b>  Stranded wire Litze Fil multi-brins	<b>4</b> IP 64  <b>7</b> IP 67  <b>8</b> IP 68	<b>1</b> Brass, blackened Messing, geschwärzt Laiton, noircie	<b>1</b> Lock-washer 	<b>H</b> with hex nut mit 6kant Mutter avec écrou 6-pans 	<b>RG36</b> common cathode only series 133R 138R for 24V only 15mA for 28V only 14mA 	<b>010</b> Standard (100 mm) Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande
<b>2</b> Brass, nickel plated Messing, vernickelt Laiton, nickelée	<b>2</b> decorative washer 	<b>N</b> with decorative nut mit Ziermutter avec écrou décoratif 							
			<b>9</b> Brass, olive drab * Messing, braunoliv * Laiton, olivebrun *						

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / \* except surface option 9 (none RoHS)

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

